


LOC I-SPI	APP CRS	Rwy Ldg	7927
109.5	043°	TDZE	592
		Apt Elev	598

ILS or LOC RWY 4
ABRAHAM LINCOLN CAPITAL (SPI)

ADF Required.				MALSR		MISSED APPROACH: Climb to 1500 then climbing left turn to 2300 direct HUSKK LOM and hold.
 ASR	When local altimeter setting not received, use Lincoln altimeter setting and increase all DA 57 feet, all MDA 60 feet, increase S-LOC and Circling Cat C/D visibility ¼ mile. For inop ALS when using Lincoln altimeter setting, increase S-LOC 4 Cats C and D visibility to 1 ¾ SM. *RVR 1800 authorized with use of FD or AP or HUD to DA (NA when using Lincoln altimeter setting).					
ATIS	SAINT LOUIS APP CON ★	SPRINGFIELD TOWER ★	GND CON	UNICOM		
127.65 270.1	126.15 323.0	121.3 (CTAF) 0 257.8	121.9 348.6	122.95		



One Minute Holding Pattern		SP LOM SPI 5.5	1500 ↑	2300 ↷	SP
		2297			
GS 3.00° TCH 56		2300			
CATEGORY	A	B	C	D	
S-ILS 4	* 792/24 200 (200-½)				
S-LOC 4	1020/24	428 (500-½)	1020/40	428 (500-¾)	
CIRCLING	1040-1 442 (500-1)	1100-1 502 (600-1)	1360-2¼ 762 (800-2¼)	1380-2½ 782 (800-2½)	

