

|                                        |                        |                             |                                       |
|----------------------------------------|------------------------|-----------------------------|---------------------------------------|
| WAAS<br>CH <b>72616</b><br><b>W34A</b> | APP CRS<br><b>345°</b> | Rwy Idg<br>TDZE<br>Apt Elev | <b>5070</b><br><b>14</b><br><b>15</b> |
|----------------------------------------|------------------------|-----------------------------|---------------------------------------|

RNAV (GPS) RWY 34

JACK BROOKS RGNL (BPT)

RNP APCH - GPS.

Baro-VNAV NA when using Orange County altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -4°C or above 54°C. When local altimeter setting not received, use Orange County altimeter setting: increase LPV DA to 346 feet; increase LNAV/VNAV DA to 347 feet and all visibilities ½ SM; increase all MDAs 40 feet.

MISSED APPROACH: Climb to 500 then climbing left turn to 3100 direct GIDDY and hold, continue climb-in-hold to 3100.

|                      |                                       |                                                 |                          |                          |                         |
|----------------------|---------------------------------------|-------------------------------------------------|--------------------------|--------------------------|-------------------------|
| ATIS<br><b>126.3</b> | HOUSTON APP CON<br><b>121.3 377.1</b> | BEAUMONT TOWER★<br><b>119.5 (CTAF)</b> <b>0</b> | GND CON<br><b>124.85</b> | CLNC DEL<br><b>118.3</b> | UNICOM<br><b>122.95</b> |
|----------------------|---------------------------------------|-------------------------------------------------|--------------------------|--------------------------|-------------------------|

