

LOC/DME I-BSM 110.95 Chan 46 (Y)	APP CRS 355°	Rwy Ldg 12250 TDZE 496 Apt Elev 542
--	------------------------	--

ILS or LOC RWY 36L
AUSTIN-BERGSTROM INTL (AUS)

DME or RADAR required.


T Simultaneous approach authorized. For inop ALS, increase S-LOC 36L Cats C/D/E visibility to RVR 6000. Inop table does not apply to S-ILS 36L all Cats.

MALS

 $\textcircled{A_4}$

MISSED APPROACH: Climb to 1000 then climbing left turn to 3500 on heading 250° and CWK VORTAC R-222 to GARDS INT/CWK 29.2 DME and hold.

D-ATIS	AUSTIN APP CON	AUSTIN TOWER	GND CON
124.4	127.225 317.65 (E)	121.0 281.5	121.9 348.6
	120.875 270.25 (S)		
	119.0 370.85 (W)		



1000 ↑	3500 hdg 250°	CWK R-222	GARDS △	VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 60).			LAMAS I-BSM 16.5 RADAR
I-BSM DME ANTENNA		FUNNN I-BSM 3.2 RADAR	JOVSA I-BSM 4.8 RADAR	BIIRD I-BSM 6.2 RADAR	CAMDY I-BSM 12.5 RADAR	5000 355° 4000 2500 2100 1600 1600 1.1 NM 2.2 NM 1.7 NM 1.3 NM 6.3 NM 4 NM GS 3.00° TCH 54	
CATEGORY		A	B	C	D	E	
S-ILS 36L		696/40 200 (200-¾)					
S-LOC 36L		900/40 404 (400-¾)	900/50 404 (400-1)				