



WAAS CH 90229 W36A	APP CRS 355°	Rwy Ldg 12250 TDZE 496 Apt Elev 542
--	------------------------	--

RNAV (GPS) Y RWY 36L

AUSTIN-BERGSTROM INTL (AUS)

RNP APCH-GPS. Simultaneous approach authorized. Use of FD or AP required during simultaneous operations. LNAV procedure NA during simultaneous operations. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -5°C or above 54°C. Inop table does not apply to LPV all Cts. For inop ALS, increase LNAV/VNAV Cat E visibility to 1½ SM, LNAV Cat E visibility to 1¼ SM.	MALS 	MISSED APPROACH: Climb to 1700 then climbing left turn to 3500 direct GARDS and hold.
---	---	---

D-ATIS 124.4	AUSTIN APP CON 127.225 317.65 (E) 120.875 270.25 (S) 119.0 370.85 (W)	AUSTIN TOWER 121.0 281.5	GND CON 121.9 348.6
------------------------	---	------------------------------------	-------------------------------



1700	3500	GARDS △	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 60).				LAMAS
CATEGORY		A	B	C	D	E	
LPV	DA	696/40 200 (200-¾)					
LNAV/ VNAV	DA	970/60 474 (500-1¼)					
LNAV	MDA	920/40	424 (400-¾)	920/50		424 (400-1)	
CIRCLING		1040-1 498 (500-1)	1120-1 578 (600-1)	1200-1¾ 658 (700-1¾)	1200-2 658 (700-2)	NA	