

|                                        |                        |                                                           |
|----------------------------------------|------------------------|-----------------------------------------------------------|
| WAAS<br>CH <b>40405</b><br><b>W09A</b> | APP CRS<br><b>093°</b> | Rwy Idg <b>4801</b><br>TDZE <b>3</b><br>Apt Elev <b>3</b> |
|----------------------------------------|------------------------|-----------------------------------------------------------|

RNAV (GPS) RWY 9

KEY WEST INTL (EYW)

RNP APCH-GPS.

▼

▲

W

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 12°C or above 54°C.  
Rwy 9 helicopter visibility reduction below ¾ SM NA. Baro-VNAV and VDP NA when using  
NQX altimeter setting. When local altimeter setting not received, use NQX altimeter setting.

MISSED APPROACH:  
Climb to 2000 direct  
BURPY and hold.

|                        |                                                 |                                               |                         |                          |                         |
|------------------------|-------------------------------------------------|-----------------------------------------------|-------------------------|--------------------------|-------------------------|
| ATIS<br><b>119.675</b> | NAVY KEY WEST APP CON ★<br><b>124.025 313.7</b> | KEY WEST TOWER ★<br><b>118.2 (CTAF) 257.8</b> | GND CON<br><b>121.9</b> | CLNC DEL<br><b>121.9</b> | UNICOM<br><b>122.95</b> |
|------------------------|-------------------------------------------------|-----------------------------------------------|-------------------------|--------------------------|-------------------------|

