

TAKEOFF OBSTACLE NOTES

Rwy 11: Light poles beginning 7' from DER, 55' left of centerline, up to 3' AGL/4863' MSL. Light poles 8' from DER, 54' right of centerline, 1' AGL/4862' MSL.

Poles beginning 251' from DER, 285' left of centerline, up to 20' AGL/4883' MSL.

Rwy 29: Vertical structure 151' from DER, 432' right of centerline, 22' AGL/4846' MSL. Navaid, tower beginning 266' from DER, 398' right of centerline, up to 43' AGL/4865' MSL.


TAKEOFF MINIMUMS

Rwy 4: NA - Obstacles.

Rwy 22: NA - Obstacles, facility reception (JNC VOR/DME).

Rwy 11: Standard with minimum climb of 235' per NM to 7400.

Rwy 29: Standard with minimum climb of 225' per NM to 8000.



25 DEC 2025

2

27 NOV 2025

NOTE: Chart not to scale

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 11: Climb on heading 116° to 6600, then climbing right turn to heading 240° until receiving JNC VOR/DME, then proceed direct JNC VOR/DME, thence

TAKEOFF RUNWAY 29: Climb on heading 296° to 7000, then climbing left turn to heading 240° until receiving JNC VOR/DME, then proceed direct JNC VOR/DME, thence

. . . . Cross JNC VOR/DME at or above MEA/MCA for route of flight. If required, continue climb in JNC holding pattern to cross JNC at or above MEA/MCA for route of flight.