

LOC/DME I-VAC

110.75

Chan **44** (Y)

APP CRS

006°

Rwy Ldg

8000

TDZE

873

Apt Elev

896

ILS RWY 36L (CAT II)

CINCINNATI/NORTHERN KENTUCKY INTL (CVG)

RNP APCH - GPS. From FECTA or SPOOD or DAWGY or RUPPP or BRCAT.
DME or RADAR required. RADAR required for procedure entry at TMORE.

ALSF-2

MISSED APPROACH: Climb to 1300 then climbing left turn to 4000 on heading 260° and on FLM VOR/DME R-314 to JADRO/FLM 43.3 DME/RADAR and hold.

D-ATIS

134.375

CINCINNATI APP CON

119.7 363.15 (090°-269°)
123.875 363.15 (270°-089°)

CINCINNATI TOWER

118.975 360.85 (18L/36R)
118.3 (9/27, 18C/36C)
133.325 (18R/36L)

GND CON

121.7

Diagram illustrating the ILS RWY 36L (CAT II) approach path and associated navigation aids. The path starts at 4000 feet, descends to 2500 feet, and then to 1300 feet. Key navigation aids include:

- LOCALIZER 110.75** (I-VAC, Chan 44(Y))
- IM** (Instrument Meteorological Conditions) at 970± feet
- EXAMS 210K** (IAF) at 4500 feet, 189° (8.7)
- CHEKO** (IAF) at 4000 feet, 096° (5.2)
- STADM** (IAF) at 4000 feet, 313° (4)
- SHULN** (IAF) at 4000 feet, 339° (4)
- WALVU** (IAF) at 5000 feet, 006° (3.2)
- TMORE** (IAF) at 7000 feet, 186° (3.2)
- SPOOD 8000** (IAF) at 8000 feet
- BEPEE** (IF) at 4000 feet, 006° (3.1)
- ROPRR** (IF) at 4500 feet, 189° (7.2)
- VUCUN 210K** (IAF) at 4000 feet, 276° (7)
- DAWGY 8000** (IAF) at 4000 feet, 313° (12.3)
- FECTA 8000** (IAF) at 4000 feet, 075° (11.1)
- JADRO 43.3** (R-314) at 134°
- FLM 43.3** (R-314) at 117.0°
- MSA CVG 25 NM** (Minimum Safe Altitude) at 3000 feet

ELEV	896	TDZE	873
TDZ/CL all Rwy's except 27 HIRL all Rwy's			

Detailed approach path diagram showing altitudes and distances:

- BEPEE** (IF) at 4000 feet, 006° (3.1)
- ROPRR** (IF) at 4500 feet, 189° (7.2)
- IM** (Instrument Meteorological Conditions) at 970± feet
- FLM R-314** at 134°
- JADRO** at 117.0°
- GS 3.00°** (TCH 55)
- Distances:** 4.9 NM, 4.9 NM, 1056'

CATEGORY	A	B	C	D
S-ILS 36L	RA 100/12 100 DA 973			

CATEGORY II ILS - SPECIAL AIRCREW & AIRCRAFT CERTIFICATION REQUIRED

Diagram showing the intersection of ILS RWY 36L and ILS RWY 36R. Key features include:

- Intersection:** 12001, 11000 X 150
- Distances:** 8000 X 150, 10000 X 150
- Altitudes:** 36C, 36R
- Navigation Aids:** A5, A6, A7, A8, A9, B, C, D, E, F, G, H, I, J, K, L, M, N, O, P, Q, R, S, T, U, V, W, X, Y, Z

COVINGTON, KENTUCKY

Amdt 2A 07AUG25

CINCINNATI/NORTHERN KENTUCKY INTL (CVG)

39°03'N-84°40'W

ILS RWY 36L (CAT II)