

WAAS CH 93612 W24A	APP CRS 241°	Rwy Ldg TDZE Apt Elev	6303 47 47
--	------------------------	-----------------------------	---------------------------------------

RNAV (GPS) RWY 24

NANTUCKET MEML (ACK)

RNP APCH - GPS.

⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -12°C or above 54°C.
⚠ For inop ALS increase LNAV/VNAV all Cats visibility to RVR 4000 and LNAV Cats C/D visibility to 1½ SM. When local altimeter setting not received, use HYA altimeter setting and increase LPV DA to 310 feet and all visibilities to RVR 2000; increase LNAV/VNAV DA to 363 feet; increase all MDAs 80 feet and LNAV visibility Cat C/D to RVR 6000 and Circling visibility Cat C/D ¼ SM. Baro-VNAV and VDP NA when using HYA altimeter setting.
For inop ALS when using HYA altimeter setting, increase LPV and LNAV/VNAV visibility all Cats to RVR 4500 and LNAV Cat C/D to 1½ SM.

SSALR



MISSED APPROACH:
Climb to 2300 direct
UFTAC and hold.

ATIS 127.5	BOSTON APP CON 126.1 318.1	NANTUCKET TOWER ★ 118.3 (CTAF) 0	GND CON 132.5	UNICOM 122.95
----------------------	--------------------------------------	--	-------------------------	-------------------------

