

ILS or LOC RWY 23

LOC/DME I-FKP 111.9 Chan 56	APCH CRS 225°	Rwy Idg 10,926 TDZE 571 Arpt Elev 571
---	-------------------------	--

[USA]

CAMPBELL AAF (FORT CAMPBELL) (KHOP)


RADAR required

▼ * When ALS inop, increase RVR to 40, vis to ¾ miles.
** When ALS inop, increase CAT AB RVR to 55, vis to 1 mile; CAT CDE RVR to 60, vis to 1½ miles.
*** Circling not authorized SE of Rwy 5-23.

SSALR
A3

MISSED APPROACH: Climb to 1200 then climbing right turn to 2500 direct AIRBE LOM/I-FKP 6.5 DME, continue climb-in-hold to 2500 (max 230 KIAS).

ATIS 125.175 308.4	APP CON 118.1 269.525	TOWER 120.9 278.8	GND CON 121.8 266.8	CLNC DEL 138.8	ASR/PAR
------------------------------	---------------------------------	-----------------------------	-------------------------------	--------------------------	---------



1200 2500 AIRBE I-FKP 6.5

VGSI and glidepath not coincident (VGSI Angle 3.00/TCH 78).

NUGLY I-FKP 4.8

225° 045° 2500

2000 2200

GS 3.00° TCH 57

2.7 NM 1.7 NM

Remain within 10 NM

CATEGORY	A	B	C	D	E
S-ILS 23 *	771/24		200	(200-½)	
S-LOC 23 **	960/24 389 (400-½)		960/35	389 (400-¾)	
*** CIRCLING	1060-1 489 (500-1)		1060-1½ 489 (500-1½)	1140-2 569 (600-2)	

ELEV 571 TDZE 571

FAF to MAP 4.4 NM

HIRL all rwys

Knots	60	90	120	150	180
Min:Sec	4:24	2:56	2:12	1:46	1:28

ILS or LOC RWY 23

SE-1, 27 NOV 2025 to 25 DEC 2025

SE-1, 27 NOV 2025 to 25 DEC 2025