

WAAS CH 53439 W16A	APP CRS 162°	Rwy Ldg TDZE 152 Apt Elev 160
--	------------------------	---

RNAV (GPS) RWY 16


NEWPORT MUNI (ONP)

⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). Baro-VNAV and VDP NA when using Tillamook altimeter setting. DME/DME RNP-0.3 NA. Inop table does not apply to LPV all Cats. When local altimeter setting not received, use Tillamook altimeter setting: increase LPV DA to 537 feet and LNAV/VNAV DA to 748 feet and all MDA 140 feet; increase LNAV/VNAV all Cats visibility and LNAV Cat C/D visibility $\frac{3}{8}$ mile and increase Circling Cat B visibility $\frac{1}{4}$ mile. For inop MALS, increase LNAV/VNAV all Cats visibility to $1\frac{1}{2}$ mile, and increase LNAV Cat A/B visibility to 1 mile, Cat C/D to $1\frac{3}{8}$ mile. For inop MALS when using Tillamook altimeter setting, increase LPV all Cats visibility to $1\frac{1}{4}$ mile, and LNAV Cat A/B visibility to 1 mile, LNAV Cat C/D to $1\frac{3}{4}$ mile. Rwy 16 helicopter visibility reduction below $\frac{3}{4}$ SM NA.

MALS

MISSED APPROACH:
Climb to 600 then
climbing right turn to
3700 direct BOILR
and hold.

AWOS-3 133.9	SEATTLE CENTER 125.8 291.7	UNICOM 122.8 (CTAF) 0
------------------------	--------------------------------------	---------------------------------



4 NM Holding Pattern		VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 51).		600	3700	BOILR
GP 3.00° TCH 55		BOILR	BUHRS	CALAX 4 NM to RW16	*1.3 NM to RW16	*LNAV only
3700		342°	162°	2100	*1480	RW16
		9.4 NM		2 NM	2.7 NM	1.3 NM
CATEGORY	A	B	C	D		
LPV DA	402-¾		250 (300-¾)			
LNAV/VNAV DA	613-1⅛		461 (500-1⅛)			
LNAV MDA	620-¾		468 (500-¾)	620-1	468 (500-1)	
CIRCLING	880-1 720 (800-1)		1000-1¼ 840 (900-1¼)	1400-3 1240 (1300-3)	1600-3 1440 (1500-3)	

