

ILS RWY 25 (CAT II)

LOC I-TYV
109.9

APCH CRS
252°

Rwy Idg **12.001**
TDZE **301**
Arpt Elev **312**

[USAF]

LITTLE ROCK AFB (KLRF)

RNP APCH: RNAV1-GPS or RADAR required.

ALSIF-2

MISSED APPROACH: Climb to 900 then climbing right turn to 3000 direct HERCK and hold.

ATIS ★
119.175 251.1

APP CON
119.5 306.2

TOWER
120.6 269.075

GND CON
132.8 275.8

CATEGORY II ILS-SPECIAL
AIRCREW & AIRCRAFT
CERTIFICATION REQUIRED

ALTERNATE MISSED APPROACH:
Climbing to 3000 fly runway heading
until 2 DME, then turn right heading 360°
expect further clearance from ATC.

4 NM HOLD 3000

HERCK

ATC RADAR required for holding above 4000' or greater than 200 KIAS.

JACKSONVILLE
Chen 29 LRF
(109.2)

R2403A
R2403B

CAT E Act: RADAR required when R-2403 active

LOCALIZER 109.9
I-TYV

294

(IAF) AALII 230K

AALII entry NA for CAT E aircraft.

2000 NOT

4 NM HOLD 4000

072° 230K 252° 072°

1800 252° (A)

HESUP RADAR LRF 6.1

(IF/IAF) BIELD LRF 10 2000

ATC RADAR required for holding above 4000' or greater than 230 KIAS.

MSA RW25 2.5 NM 3200

EMERG SAFE ALT 100 NM 4000

900 3000 HERCK

900 3000 HERCK

LRF TACAN

HESUP RADAR LRF 6.1

BIELD LRF 10 4000 2000

072° 252° 1800

GS 3.00° TCH 56

4.6 NM

993

CATEGORY A B C D E

S-ILS 25 RA 94/12 100 DA 401

HIRL Rwy 07-25
TDZL/RCLS Rwy 25

ASSAULT STRIP 072° 3361 x 60

12.001 x 150

TWR

SC-1, 27 NOV 2025 to 25 DEC 2025

SC-1, 27 NOV 2025 to 25 DEC 2025

JACKSONVILLE, ARKANSAS

34° 55' N-92° 09' W

LITTLE ROCK AFB (KLRF)

ILS RWY 25 (CAT II)

Amdt 1 18APR24