

LOC I-AWO	APP CRS	Rwy Idg	5332
111.5	342°	TDZE	135
		Apt Elev	142

LOC RWY 34

ARLINGTON MUNI (AWO)

ADF required. When local altimeter setting not received, use Whidbey Island NAS (Ault Field) altimeter setting: increase all MDA 80 feet and visibility S-34 Cats C and D and Circling Cats B and C ¼ SM. For inop MALS, increase S-34 Cats C and D visibility to 1 ¾.

MALS

MISSED APPROACH: Climb to 1000 then climbing left turn to 2000 direct WATON LOM and hold.

AWOS-3PT 135.625	SEATTLE APP CON 128.5 306.9	CLNC DEL 121.725	CTAF 122.725 0
---------------------	--------------------------------	---------------------	-------------------

ADF REQUIRED

LOCALIZER 111.5
I-AWO

271±

588

545

617

2371

3094

3000

2000

1000

5340

2000

1000

3000

LOM/IAF WATON 382 AW : - -

758

1700

342° (6)

207°

037°

R-037

(IF) SAVOY INT

R-162

2000 NoPT

037°

(6.1)

IAF PAINE 110.6 PAE : - - -
Chan 43

MSA AW 25 NM

8100

2100

210°

330°

Remain within 10 NM

AW LOM 6000

2000

162°

342°

1700

3.05°

TCH 46

4.7 NM

CATEGORY	A	B	C	D
S-34	580-¾	445 (500-¾)	580-1	445 (500-1)
CIRCLING	840-1 698 (700-1)	900-1 758 (800-1)	1000-2½ 858 (900-2½)	1040-3 898 (900-3)

ELEV 142

TDZE 135

MIRL Rwy 16-34

REIL Rwy 16 0

REIL Rws 11 and 29

91

5332 X 100

3498 X 75

186

34

342°

FAF to MAP 4.7 NM

Knots	60	90	120	150	180
Min:Sec	4:42	3:08	2:21	1:53	1:34

ARLINGTON, WASHINGTON

Amtd 5B 24MAR22

48°10'N-122°10'W

ARLINGTON MUNI (AWO)

LOC RWY 34