

WAAS CH 93836 W12A	APP CRS 127°	Rwy Ldg TDZE Apt Elev 7506 4457 4457
--	------------------------	--

RNAV (GPS) RWY 12


LAS CRUCES INTL (LRU)

⚠


For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -12 °C (11°F) or above 49°C (120°F). DME/DME RNP-0.3 NA. Helicopter visibility reduction below ¾ SM NA. Baro-VNAV and VDP NA when using Deming altimeter setting. When local altimeter setting not received, use Deming altimeter setting: increase LPV DA to 4821 feet and LNAV/VNAV DA to 4824 feet and all visibilities ½ mile; increase all MDA 120 feet and visibility Cat C and D ½ mile.

MISSED APPROACH: Climb to 5800 then climbing right turn to 8100 direct IPATE and hold.

AWOS-3 119,025	ALBUQUERQUE CENTER 128.2 285.5	UNICOM 122.7 (CTAF) 0
--------------------------	--	---------------------------------



ELEV 4457	D	TDZE 4457
------------------	----------	------------------



REIL Rwy 12
HIRL Rwy 12-30 0
MIRL Rwy 4-22 and 8-26 0

7 NM Holding Pattern IPATE HUXEM WEKVO 2.1 NM to RW12 8100 ← 307° 127° → GP 3.00° TCH 55 6600 6600 *5180 6 NM 4.5 NM 0.9 1.2 NM RW12 5800 ↑ 8100 ↗ IPATE ✦ *LNAV only.				
CATEGORY	A	B	C	D
LPV DA	4707-¾ 250 (300-¾)			
LNAV/VNAV DA	4710-¾ 253 (300-¾)			
LNAV MDA	4900-1	443 (500-1)	4900-1¾	443 (500-1¾)
CIRCLING	4900-1 443 (500-1)	5040-1 583 (600-1)	5320-2½ 863 (900-2½)	5320-2¾ 863 (900-2¾)