

WAAS
CH **86902**
W24A

APP CRS
241°

Rwy Idg
TDZE **16**
Apt Elev **18**

RNAV (GPS) RWY 24

BOWERMAN FLD (HQM)

▼

▲

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -6°C (22°F) or above 43°C (109°F). When local altimeter setting not received, procedure NA. Circling NA northwest of Rwy 6-24. DME/DME RNP-0.3 NA. For inoperative MALSR, increase LPV Cat C visibility to ¾ mile and LNAV Cat C visibility to 2½ miles.

MALSR

MISSED APPROACH:
Climb to 2600 direct ZUNAD and hold.

ASOS 135.775	SEATTLE CENTER 128.3 269.0	UNICOM 122.7 (CTAF) 0
------------------------	--------------------------------------	---------------------------------

MSA RW24 25 NM
4600

Procedure NA for arrivals at ULESS on V27 northeast bound. (IAF) ULESS

2900 NoPT 203° (170.4) 4 NM

061° 241° 2900 NoPT 267° (9.6) (IAF) SOUPY

(FAF) NEYDI 2100 241° (6.3)

(IF/IAF) LAMMB

FODUL 2.3 NM to RW24

Δ 722

Δ 300

ZUNAD

061° 241° 4 NM

Δ 844

Δ 1091

3400 014° (28.8)

PUGIC Procedure NA for arrivals at PUGIC on V27 southeast bound.

ELEV 18 TDZE 16

ELEV 18

TDZE 16

2600 ZUNAD

* LNAV Only.

RW24

FODUL 2.3 NM to RW24

NEYDI 2100

LAMMB

4 NM Holding Pattern

061° 241° 2900

GP 3.50° TCH 55

CATEGORY	A	B	C	D
LPV DA	226-½ 210 (300-½)		286-½ 270 (300-½)	NA
LNAV/VNAV DA	676-1½ 660 (700-1½)			NA
LNAV MDA	800-½ 784 (800-½)	800-¾ 784 (800-¾)	800-1¾ 784 (800-1¾)	NA
CIRCLING	800-1 782 (800-1)	800-1¼ 782 (800-1¼)	800-2¼ 782 (800-2¼)	NA

HOQUIAM, WASHINGTON
Amdt 2E 07OCT21

46°58'N-123°56'W

BOWERMAN FLD (HQM)
RNAV (GPS) RWY 24