

WAAS CH 40420 W18A	APP CRS 178°	Rwy Idg 5998 TDZE 206 Apt Elev 206
--	------------------------	---

RNAV (GPS) RWY 18
PINEBLUFF RGNL/GRIDER FLD (PBF)

RNP APCH - GPS.

V Baro-VNAV and VDP NA when using Stuttgart altimeter setting. For uncompensated
A Baro-VNAV systems, LNAV/VNAV NA below -10°C or above 54°C. When local
altimeter setting not received, use Stuttgart altimeter setting and increase LPV DA to 534 feet;
increase LNAV/VNAV DA to 723 feet and all visibilities ½ SM. Increase all MDAs 80 feet and
LNAV visibility Cat C/D ¾ SM, and Circling visibility Cat C/D ¼ SM. For inop ALS, increase
LNAV Cats A/B visibility to 1 SM and Cats C/D visibility to 1 ½ SM. For inop ALS
when using Stuttgart altimeter setting, increase LPV all Cats visibility to 1 SM; increase
LNAV/VNAV all Cats visibility to 1 ½ SM; increase LNAV Cats C/D visibility 1 ¾ SM.

MALSR

ASOS
120.775

LITTLE ROCK APP CON
119.85 353.6

CLNC DE
119.85

UNICOM
123.0 (CTAF) **L**

