

WAAS CH 42832 W20A	APP CRS 203°	Rwy Ldg TDZE Apt Elev	3997 339 342
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 20

CAPE GIRARDEAU RGNL (CGI)


RNP APCH-GPS.

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. When local altimeter setting not received, use Cairo altimeter setting and increase LPV DA to 637 feet and all visibilities $\frac{1}{8}$ SM; increase LNAV/VNAV DA to 652 feet; increase all MDAs 60 feet; increase LNAV and Circling visibility Cats C and D $\frac{1}{4}$ SM. Rwy 20 helicopter visibility reduction below $\frac{3}{4}$ SM NA. Baro-VNAV and VDP NA when using Cairo altimeter setting.

MISSED APPROACH: Climb to 3000 direct ZUGUB and hold.

ASOS 120.55	MEMPHIS CENTER 133.65 292.15	CAPE GIRARDEAU TOWER ★ 125.525 (CTAF) 0	GND CON 124.7	UNICOM 122.95
-----------------------	--	--	-------------------------	-------------------------



3000

↑

ZUGUB

✦

ORUCE

2.1 NM to RW20

UFAVO

2000

UWALE

4 NM Holding Pattern

023° →

← 203°

3500

GP 3.00°

TCH 43

1.4 NM

0.7

3 NM

6 NM

1040

2000

1.4 NM to RW20

CATEGORY	A	B	C	D
LPV DA	589-1 250 (300-1)			
LNAV/VNAV DA	604-1 265 (300-1)			
LNAV MDA	840-1 501 (500-1)		840-1 $\frac{3}{8}$ 501 (500-1 $\frac{3}{8}$)	
CIRCLING	860-1 518 (600-1)	960-1 618 (700-1)	1000-1 $\frac{3}{4}$ 658 (700-1 $\frac{3}{4}$)	1080-2 $\frac{1}{4}$ 738 (800-2 $\frac{1}{4}$)

MIRL Rwy 2-20

HIRL Rwy 10-28