

WAAS CH 93730 W19B	APP CRS 194°	Rwy Ldg 5004 TDZE 787 Apt Elev 787
--	------------------------	---

RNAV (GPS) Z RWY 19

RUTLAND/SOUTHERN VERMONT RGNL (RUT)

RNP APCH - GPS.


V Circling NA northeast of Rwy 19 and 31. Circling Rwy 13, 31 NA at night. Inop table does not apply to LNAV/VNAV all Cts, Baro-VNAV NA. For inop ALS, do not use LPV all Cts visibility to 1½ miles. VDP NA when using VSF altimeter setting. For inop ALS while using VSF altimeter setting, increase LPV all Cts visibility to 1½ miles. Inop table does not apply when using VSF altimeter setting to LNAV/VNAV all Cts and LNAV Cat C. When local altimeter setting not received, use VSF altimeter setting and increase LPV DA to 1281 feet and all visibilities ½ SM; increase LNAV/VNAV DA to 2230 feet; increase all MDAs 80 feet and LNAV visibility Cat C ½ SM.

MALSR



MISSED APPROACH: Climb to 1500 then climbing right turn to 5700 direct JOGIM and hold, continue climb-in-hold to 5700. Missed approach requires minimum climb of 420 feet per NM to 3200; if unable to meet climb gradient, see RNAV (GPS) Y Rwy 19.

AWOS-3PT 118.375	BOSTON CENTER 135.7 282.2	UNICOM 122.8 (CTAF) 
----------------------------	-------------------------------------	---

[illegible]

RNAV (GPS) Z RWY 19