

LOC/DME I-BBJ

110.9

Chan 46

APP CRS

264°

Rwy Ldg

5500

TDZE

671

Apt Elev

672

ILS or LOC RWY 26

KEOKUK MUNI (EOK)

DME required for LOC only.

NA

Circling Rwy 32 NA at night. Inop table does not apply to S-ILS 26. VDP NA when using Burlington altimeter setting. When local altimeter setting not received, use Burlington altimeter setting and increase S-ILS 26 DA to 927 feet, increase all MDAs 60 feet and Circling visibility Cat C ¼ SM. For inop ALS, increase S-LOC 26 Cats A and B visibility to 1 SM, and Cat C to ¾ SM. For inop ALS when using Burlington altimeter setting, increase S-LOC 26 all Cats visibility to 1 SM.

MALSR

MISSED APPROACH:

Climb to 2600 then right turn direct BRL VOR/DME and hold.

AWOS-3 118.375	KANSAS CITY CENTER 126.225 317.775	UNICOM 122.8 (CTAF) 0
-------------------	---------------------------------------	--------------------------

2600

BRL

SLAPS I-BBJ 6.4

2400

084°

264°

2400

2400

1400

0.8 NM

1.3 NM

3.1 NM

GS 3.00°

TCH 40

CATEGORY	A	B	C	D
S-ILS 26	871-¾	200 (200-¾)		NA
S-LOC 26	980-¾	309 (400-¾)		NA
CIRCLING	1180-1 508 (600-1)	1220-1 548 (600-1)	1220-1½ 548 (600-1½)	NA

REIL Rwy 8, 14, and 32 0
MIRL Rwy 8-26 and 14-32 0

KEOKUK, IOWA

Amcl 1 20APR23

40°28'N-91°26'W

KEOKUK MUNI (EOK)

ILS or LOC RWY 26