

APP CRS	Rwy Ldg	10302
016°	TDZE	1314
	Apt Elev	1333

RNAV (RNP) Z RWY 1L

WICHITA DWIGHT D EISENHOWER NTL (ICT)

RNP AR APCH

Simultaneous approach authorized. Use of FD or AP providing RNAV track guidance required during simultaneous operations. For uncompensated Baro-VNAV systems, procedure NA below -15°C or above 54°C. For inop ALS, increase RNP 0.15 all Cats visibility to RVR 4500 and RNP 0.30 all Cats visibility to RVR 5500.

ALSF-2

MISSED APPROACH:
Climb to 4200 on track 016° to ACUBO and hold.

ATIS
125.15

WICHITA APP CON
126.7 353.5

WICHITA TOWER
118.2 257.8

GND CON
121.9 348.6

ELEV 1333

TDZE 1314

HIRL all Rwy's

REIL Rwy's 14 and 32

TDZ/CL Rwy 1L

CATEGORY	A	B	C	D
RNP 0.15 DA	1626/28 312 (300-5%)			
RNP 0.30 DA	1676/35 362 (400-5%)			

AUTHORIZATION REQUIRED

NC-2, 27 NOV 2025 to 25 DEC 2025

NC-2, 27 NOV 2025 to 25 DEC 2025