

WAAS CH 86305 W22A	APP CRS 224°	Rwy Idg 5200 TDZE 83 Apt Elev 83
--	------------------------	---

RNAV (GPS) RWY 22

HANCOCK COUNTY/BAR HARBOR (BHB)

RNP APCH - GPS.


⚠ Baro-VNAV NA when using Bangor altimeter setting. When local altimeter setting not received, use Bangor altimeter setting and increase LPV DA to 366 feet; increase LNAV/VNAV DA to 780 feet and all visibilities ¼ SM. Increase all MDAs 100 feet and LNAV visibility Cats C/D, and Circling visibility Cats C/D ¼ SM. When using Bangor altimeter setting, inop table does not apply to LNAV/VNAV all Cats and LNAV Cat C. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 49°C. Circling Rwy 17, 35 NA at night.

MALSF



MISSED APPROACH:
Climb to 2900 direct
WHAME and hold.


AWOS-3PT 118.35	BANGOR APP CON 133.6 284.65	CLNC DEL 119.9	UNICOM 123.0 (CTAF)	122.70
---------------------------	---------------------------------------	--------------------------	-------------------------------	---------------




MISSSED APCH FIX
WHAME

2900	WHAME
	

* LNAV only.



CATEGORY		A		B		C		D	
LPV	DA			283- $\frac{3}{4}$		200 (200- $\frac{3}{4}$)			
LNNAV/ VNAV	DA			697-1 $\frac{1}{2}$		614 (700-1 $\frac{1}{2}$)			
LNNAV	MDA	580- $\frac{3}{4}$		497 (500- $\frac{3}{4}$)		580-1 $\frac{1}{4}$ 497 (500-1 $\frac{1}{4}$)		580-1 $\frac{1}{2}$ 497 (500-1 $\frac{1}{2}$)	
CIRCLING		600-1 517 (600-1)		720-1 637 (700-1)		720-1 $\frac{3}{4}$ 637 (700-1 $\frac{3}{4}$)		840-2 $\frac{1}{2}$ 757 (800-2 $\frac{1}{2}$)	



BAR HARBOR, MAINE

Amdt 1C 11AUG22

HANCOCK COUNTY/BAR HARBOR (BHB)

44°27'N-68°22'W

RNAV (GPS) RWY 22