


APP CRS	Rwy Ldg	4600
053°	TDZE	368
	Apt Elev	368

RNAV (GPS) RWY 4L
NENANA MUNI (ENN)(PANN)

RNP APCH - GPS.	MISSED APPROACH: Climb to 5000 direct JASEK and hold, continue climb-in-hold to 5000.
Procedure NA at night. Circling NA northwest of Rwy 4L-22R. Circling NA to Rwys 4R, 22L, 4W and 22W. Rwy 4L helicopter visibility reduction below 1 SM NA. When local altimeter setting not received, use FAI/PAFA altimeter setting and increase all MDAs 100 feet and LNAV visibility Cats C and D 3/4 SM, and Circling visibility Cats C and D 1/4 SM.	

ASOS 125.2	FAIRBANKS APP CON 125.35 363.2	FAIRBANKS RADIO 122.5	CTAF 122.10
---------------	-----------------------------------	--------------------------	----------------



ZENEX 3000 053° EKUCO 2000 3.00° TCH 35 HECKL 1260 2.5 NM to RW04L FORIT 4 NM 2.3 NM 2.5 NM 0.3 A B C D 740-1 372 (400-1) 820-1 452 (500-1) 1140-2¼ 772 (800-2¼) 1140-2½ 772 (800-2½)					
CATEGORY	A	B	C	D	
LNAV MDA	740-1 372 (400-1)				
CIRCLING	820-1 452 (500-1)		1140-2¼ 772 (800-2¼)	1140-2½ 772 (800-2½)	

