

ILS Z or LOC Z RWY 20R
KENAI MUNI (ENA) (PAEN)

T Circling NA to Rwy 2W and 20W. Circling Rwy 2R, 20L
NA at night.
RVR 1800 authorized with use of FD or AP or HUD to DA.



MISSED APPROACH: Climb to 2200 on ENA
VOR/DME R-192 to DIXIT/10 DME and hold.

Use I-ENA DME when on the localizer course.

The diagram illustrates the I-ENA DME system. It shows a localizer course (LOC) with a 1.2 NM segment and a 2.8 NM segment. The DME stations are located at 1.4, 2.6, 5.4, and 11.8 NM from the localizer. The localizer course is labeled with a 196° heading. The DME stations are labeled with their respective frequencies: 1.4, 2.6, 5.4, and 11.8. The diagram also shows a holding pattern (One Minute Holding Pattern) at the 11.8 NM station, with a 016° heading and a 196° heading. The holding pattern is labeled with a 1400 frequency. The diagram also shows a 1400 frequency at the 5.4 NM station. The diagram includes a table with the following information:

CATEGORY	A	B	C	D
S-ILS 20R#	298/24 200 (200-1/2)			
S-LOC 20R	520/24 422 (500-1/2)		520/40 422 (500-3/4)	
CIRCLING	560-1 460 (500-1)	580-1 480 (500-1)	580-1 1/2 480 (500-1 1/2)	680-2 580 (600-2)