

# RNAV (GPS) RWY 2L

## KENAI MUNI (ENA) (PAEN)

**⚠** Baro-VNAV NA when using Soldotna altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C (0°F) or above 54°C (130°F). When local altimeter setting not received, use Soldotna altimeter setting: increase LPV DA to 366 feet and LNAV/VNAV DA to 429 feet and all MDA 40 feet; increase LPV and LNAV/VNAV visibility all Cats and LNAV Cat C/D visibility ½ mile; increase Circling Cat D visibility ¼ mile. VDP NA when using Soldotna altimeter setting. Circling RWY 2R, 20L NA at night. Circling RWY 2W, 20W NA.

**MISSED APPROACH:**  
Climb to 2000 direct  
TBONE and hold.

KENAI RADIO  
122.65

2000 to FOPTY  
196° (14.6)

5 NM.

- (IF/IAF)  
FOPTY

2000 NoPT  
313°

(IAF)  
KASSI

MSA RW02L 25 NM

3500

TDZE 94

FOPTY

|      |       |
|------|-------|
| 2000 | TBONE |
|------|-------|



\* LNAV only

$$\underline{2000} \begin{array}{c} \leftarrow 196^\circ \\ \hline 016^\circ \rightarrow \end{array}$$

-014-

CAPRU

\*1.1 NM to

W02L

GP 3.00°  
TCH 53

✓

—



| CATEGORY         | A                    | B                    | C                      | D                    |
|------------------|----------------------|----------------------|------------------------|----------------------|
| LPV DA           | 344-¾ 250 (300-¾)    |                      |                        |                      |
| RNAV/<br>VNAV DA | 407-1 313 (400-1)    |                      |                        |                      |
| RNAV MDA         | 480-1 386 (400-1)    |                      | 480-1½ 386 (400-1½)    |                      |
| CIRCLING         | 560-1<br>460 (500-1) | 580-1<br>480 (500-1) | 580-1½<br>480 (500-1½) | 740-2<br>640 (700-2) |

REIL Rwy 2L (L)  
HIRL Rwy 2L-2