

WAAS CH 82004 W05A	APP CRS 050°	Rwy Ldg 10960 TDZE 93 Apt Elev 93
--	------------------------	--

RNAV (GPS) RWY 5

KINSTON RGNL JETPORT AT STALLINGS FLD (ISO)

RNP APCH - GPS.

▼

▲


For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -1.5°C or above 54°C. Baro-VNAV and VDP NA when using GSB altimeter setting. When local altimeter setting not received, use GSB altimeter setting: increase LPV DA to 336 feet; increase LNAV/VNAV DA to 529 feet and all visibilities to RVR 4000; increase all MDAs 60 feet and LNAV visibility Cat C/D to RVR 4500 and Circling visibility Cat D ¼ SM. For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 4500 and LNAV Cats A and B visibility to RVR 5500 and Cats C and D to RVR 6000. For inop ALS when using GSB altimeter setting, increase LNAV Cats A and B visibility to RVR 5500 and Cats C and D to 1 ⅜ mile.

* RVR 1800 authorized with use of FD or AP or HUD to DA (NA when using GSB altimeter setting).

MALSRL

MISSED APPROACH:
Climb to 2500 direct
WINTI and hold.

AWOS-3 132.75	SEYMOUR JOHNSON APP CON ★ 127.3 273.6	KINSTON TOWER ★ 120.6 (CTAF) 0 335.55	GND CON 121.9	UNICOM 122.95
-------------------------	---	---	-------------------------	-------------------------



5 NM Holding Pattern		UHIRO	ZOMAV	ZATVA	RW05
14000 ← 230°		2100 → 050°	2100	2.4 NM to RW05	1 NM to RW05
GP 3.00°		TCH 59	900		
		4.8 NM	3.7 NM	1.4 NM	1 NM
CATEGORY	A	B	C	D	
LPV DA*	293/24		200 (200-½)		
LNAV/VNAV DA	486/35		393 (400-⅝)		
LNAV MDA	480/24	387 (400-½)		480/35	387 (400-⅝)
CIRCLING	580-1	487 (500-1)		700-1¾ 607 (700-1¾)	740-2 647 (700-2)

