

WAAS CH 70615 W27A	APP CRS 275°	Rwy Ldg 6520 TDZE 974 Apt Elev 981
--	------------------------	---

RNAV (GPS) RWY 27L
OAKLAND COUNTY INTL (PTK)


RNP APCH.

- T** For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 47°C (116°F).
A Baro-VNAV and VDP NA when using Coleman A Young altimeter setting. Circling Rwy 9L, 36 NA at night. When local altimeter setting not received, use Coleman A Young 120 ft altimeter setting and increase LPV DA to 1279 feet, LNAV/VNAV DA to 1568 and all MDA 120 feet, increase LPV and LNAV/VNAV all cats visibility $\frac{1}{4}$ SM, LNAV Cat C/D, and Circling Cat C/D visibility $\frac{1}{2}$ SM.


MISSED APPROACH:
Climb to 3000 direct
EDESE and hold.

ATIS 125.025	DETROIT APP CON 132.35 284.0	PONTIAC TOWER ★ 120.5 (CTAF) 0	GND CON 121.9	UNICOM 122.95
------------------------	--	--	-------------------------	-------------------------

Procedure NA for arrivals on FNT VORTAC
airway radials 076 CW 097.



ELEV 981	D	TDZE 974
----------	----------	----------



HIRL Rwy 9R-27L **L**
MIRL Rwy 9L-27R
REIL Rwy 27L **L**
REIL Rwy 9L and 27R