

ILS or LOC RWY 24
MC CLELLAN-PALOMAR (CRQ)

- MALSR
-  

MISSED APPROACH: Climb to 3000 on heading 245° and on OCN VORTAC R-145 to OCN VORTAC and hold.

Diagram illustrating the layout of HIRL RWY 6-24. The runway is oriented at 245°. Key features include:

- Runway dimensions: 4897 X 150.
- Navigation aids: TWIR (Tactical Warning Receiver), AS (Automatic Surveillance), and H (Height).
- Other markings: 24, 245°, and various symbols indicating specific points or structures along the runway axis.

3000 ↑ hdg 245°	OCN R-145	OCN ☐	WUNUB I-CRQ 8 CIDRU I-CRQ 6.5 HUSET I-CRQ 4.2 ESCON INT I-CRQ 10.4 245° 3300 2600 2300 1640* GS 3.20° TCH 55					
*LOC only		*I-CRQ 2.7	I-CRQ 0.9	1.8 NM	1.5 NM	2.4 NM	1.5 NM	2.4 NM
CATEGORY	A		B		C		D	
S-ILS 24	527/40 201 (200-¾)		576/40 250 (300-¾)				NA	
S-LOC 24	1000/40 674 (700-¾)		1000-1½ 674 (700-1½)				NA	
CIRCLING	1000-1 669 (700-1)		1020-1 689 (700-1)		1260-2¾ 929 (1000-2¾)		NA	