

|                                        |                        |                                                               |
|----------------------------------------|------------------------|---------------------------------------------------------------|
| WAAS<br>CH <b>70302</b><br><b>W16A</b> | APP CRS<br><b>161°</b> | Rwy Ldg <b>6200</b><br>TDZE <b>192</b><br>Apt Elev <b>192</b> |
|----------------------------------------|------------------------|---------------------------------------------------------------|

## RNAV (GPS) RWY 16L

MANASSAS RGNL/HARRY P DAVIS FLD (HEF)

RNP APCH - GPS.

**T** For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or  
**A** above 54°C. For inop ALS, increase LNAV Cat C/D visibility to 13% SM.

MALS<sup>R</sup>

**MISSED APPROACH:** Climb to 700 then climbing right turn to 3000 direct CSN VORTAC and hold.

|                 |                                    |                                           |                  |                   |
|-----------------|------------------------------------|-------------------------------------------|------------------|-------------------|
| ATIS<br>125.175 | POTOMAC APP CON<br>128.525 306.925 | MANASSAS TOWER ★<br>133.1 (CTAF) 0 360.75 | GND CON<br>121.8 | CLNC DEL<br>120.2 |
|-----------------|------------------------------------|-------------------------------------------|------------------|-------------------|