MYCAR FIVE DEPARTURE (RNAV)

ATIS 125.25 CLNC DEL 339.8 121.9 (when too GND CON 121.9 339.8 RNAV 1 - DME/DME/IRU or GPS.
RADAR required.


TOP ALTITUDE: ASSIGNED BY ATC


121.9 (when tower closed)
GND CON
121.9 339.8

LAKEFRONT TOWER *
124.3 (CTAF) 339.8

CLEVELAND DEP CON
125.35 346.325

NOTE: Rwy 6R/24L: Takeoff minimums NA when control tower closed.





TAKEOFF MINIMUMS:

Rwys 6L, 24R: Standard with minimum climb of 500' per NM to 1100.
Rwy 6R: Standard with minimum climb of 500' per NM to 1100. NA when control tower closed.

Rwy 24L: 400-1% or standard with minimum climb of 757' per NM to 1000. NA when control tower closed.

NOTE: Chart not to scale.



27 NOV 2025 to

25 DEC 2025

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAYS 6L/R: Climb on heading 065° to 1100, then on heading 350° or as assigned by ATC, maintain 2000 (do not climb above 2000) for RADAR vectors to cross OCIFR at or above 3000, thence....

TAKEOFF RUNWAYS 24L/R: Climb on heading 245° to 1100, then right turn on heading 350° or as assigned by ATC, maintain 2000 (do not climb above 2000) for RADAR vectors to cross OCIFR at or above 3000, thence....

....on track 079° to cross WHARS at or below 14000, then on track 079° to MYCAR. Maintain ATC assigned altitude, expect filed altitude ten minutes after departure.