

LOC I-SQK
108.35

APP CRS
185°

Rwy Idg
6503
TDZE
866
Apt Elev
866

ILS or LOC RWY 18

METTEL FLD (CEV)

ADF required.

NA

Circling NA to Rwys 4 and 22. For inop MALSR, increase S-LOC 18 Cats C/D visibility to 1½ mile. When local altimeter setting not received, use James M Cox Dayton Intl altimeter setting and increase ILS DA to 1237 feet and visibility all Cats to ¾ mile, increase all MDA 140 feet and LOC Cats C/D visibility to 1½ mile, and Circling Cat B visibility to 1¼ miles and Cat C to 2¾ miles and Cat D to 3 miles. When using James M Cox Dayton Intl altimeter setting: for inop MALSR, increase S-ILS 18 all Cats visibility to 1 mile and increase S-LOC 18 Cat A/B visibility to 1 mile and Cat C/D to 1½ mile.

MALSR

MISSED APPROACH:
Climb to 2800 then
left turn direct SQ LOM
and hold.

AWOS-3 118.325	COLUMBUS APP CON 134.45 352.05	UNICOM 122.8 (CTAF) 1
-------------------	-----------------------------------	--------------------------

2800	SQ	SQ LOM	Remain within 10 NM	
2255	005°	2800	GS 3.00° TCH 46	
2300	185°			
4.2 NM				
CATEGORY	A	B	C	D
S-ILS 18	1116-½	250 (300-½)		
S-LOC 18	1280-½	414 (500-½)	1280-¾	414 (500-¾)
CIRCLING	1440-1 574 (600-1)	1540-1 674 (700-1)	1620-2¼ 754 (800-2¼)	1620-2½ 754 (800-2½)

CONNERSVILLE, INDIANA

METTEL FLD (CEV)

Amtd 1 03JAN19

39°42'N-85°08'W

ILS or LOC RWY 18

EC-2, 27 NOV 2025 to 25 DEC 2025

EC-2, 27 NOV 2025 to 25 DEC 2025