

WAAS CH 93620 W12A	APP CRS 123°	Rwy Idg TDZE 2294 Apt Elev 2296
--	------------------------	---

RNAV (GPS) RWY 12


WOKAL FLD/GLASGOW-VALLEY COUNTY (GGW)

RNP APCH

For uncompensated Baro-VNAV systems, LNAV-VNAV NA below -14°C or above 54°C. When local altimeter setting not received, use Wolf Point altimeter setting and increase LPV DA to 2685 feet and visibility all Cats ½ SM; Increase LNAV/VNAV DA to 2728 feet and visibility all Cats ½ SM; increase all MDAs 160 feet and LNAV Cats C/D and Circling Cat D visibility ½ SM, Circling Cat C ¼ SM. Baro-VNAV and VDP NA when using Wolf Point altimeter setting.

MISSED APPROACH:
Climb to 6000 direct
EZCUP and on track
077° to NEGAE
and hold.

ASOS 135.175	SALT LAKE CENTER 126.85 305.2	UNICOM 122.8 (CTAF) 0
------------------------	---	---------------------------------



5 NM Holding Pattern		ATCHY	6000	EZCUP	NEGAE
14000 ← 303°		123° →	4000	GOSSI 1.7 NM to RW12	*2860
5000		123°	4000	*0.9 NM to RW12	RW12
GP 3.00° TCH 40		6.1 NM	3.5 NM	0.8	0.9
CATEGORY	A	B	C	D	
LPV DA	2544-7/8		250 (300-7/8)		
LNAV/VNAV DA	2587-1		293 (300-1)		
LNAV MDA	2600-1	306 (400-1)	2600-7/8	306 (400-7/8)	
CIRCLING	2780-1	484 (500-1)	2780-1½ 484 (500-1½)	2900-2 604 (700-2)	

