

WAAS
CH **40421**
W23A

APP CRS
233°

Rwy Ldg
TDZE **1292**
Apt Elev **1313**

RNAV (GPS) RWY 23

MOORE-MURRELL (MOR)


▼

▲ NA

Baro-VNAV NA when using Mc Ghee Tyson altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C (2°F) or above 35°C (95°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Mc Ghee Tyson altimeter setting and increase all DA 133 feet and all MDA 140 feet, increase LPV all Cats visibility to 1½ miles, LNAV/VNAV all Cats visibility to 5 miles, LNAV and Circling Cat B visibility to 1½ miles and LNAV Cats C and D and Circling Cat C visibility to 3 miles.

MISSED APPROACH:
Climb to 5000 direct SIQCU and on track 299° to MALIN and hold.

AWOS-3 126.725	KNOXVILLE APP CON 132.8 360.8	UNICOM 122.8(CTAF) 0
--------------------------	---	--------------------------------



ELEV 1313

TDZE 1292

5000

SIQCU

tr 299°

MALIN

5718 x 100

0.7% UP

233°

WINRI 3200

233°

234°

054°

4300

GP 3.00°

TCH 41

	A	B	C	D
LPV DA	1589-1 297 (300-1)			
LNAV/VNAV DA	2387-4 1095 (1100-4)			
LNAV MDA	2200-1¼ 908 (900-1¼)		2200-2½ 908 (900-2½)	
CIRCLING	2200-1¼ 887 (900-1¼)		2200-2¾ 2420-3 887 (900-2¾) 1107 (1200-3)	