

WAAS CH 86801 W03A	APP CRS 026°	Rwy Idg 5502 TDZE 315 Apt Elev 315
--	------------------------	---

RNAV (GPS) RWY 3

SIKESTON MEML MUNI (SIK)



RNP APCH.

NA

Rwy 3 helicopter visibility reduction below ¾ SM NA. Baro-VNAV NA when using Cape Girardeau altimeter setting. For uncompensated Baro-VNAV systems, procedure NA below -15°C or above 54°C. When local altimeter setting not received, use Cape Girardeau altimeter setting and increase all DA 49 feet and all MDA 60 feet. Increase LNAV and Circling Cat C/D visibility ¼ SM.

MISSED APPROACH: Climb to 2200 direct IBEFY and hold.

AWOS-3 119.175	MEMPHIS CENTER 133.65 292.15	UNICOM 122.8 (CTAF)
--------------------------	--	-------------------------------



CUXID (NoPT)		HOLD 6000 2000		4 NM		ELEV 315		TDZE 315	
4 NM Holding Pattern CUXID GAYEV 2000 2000 GP 3.00° TCH 45 6.8 NM 3.6 NM 1.6 2200 IBEFY YEKUD 1.6 NM to RW03 *LNAV only *860 RW03				206° 026° 026° 2000 5500 x 100 026° to RW03 REIL Rwy 21 MIRL Rwy 3-21					
CATEGORY	A	B	C	D					
LPV DA	629-1 314 (400-1)								
LNAV/VNAV DA	769-1½ 454 (500-1½)								
LNAV MDA	720-1	405 (500-1)	720-1½	405 (500-1½)					
CIRCLING	840-1 525 (600-1)	860-1 545 (600-1)	1080-2¼ 765 (800-2¼)	1160-2¾ 845 (900-2¾)					

