

RNP APCH-GPS.

▼


▲

Baro-VNAV and VDP NA when using Tracy Muni altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 36°C. When local altimeter setting not received, use Tracy Muni altimeter setting and increase LPV DA to 1441 feet; LNAV/VNAV DA to 1548 and all Cats visibilities ½ SM; increase all MDA 60 feet, LNAV visibility Cat C/D ½ SM and Circling visibility Cat C/D ¼ SM. For inop ALS, increase LNAV/VNAV all Cats visibility to ⅔ SM, and LNAV Cat C/D visibility to 1 SM. For inop ALS when using Tracy Muni altimeter setting, increase LNAV/VNAV all Cats visibility to 1 SM.

MALSR

MISSED APPROACH:
Climb to 3000 direct BOPMY and hold.

AWOS-3PT 120.150	MINNEAPOLIS CENTER 127.1 290.2	GCO 121.725	UNICOM 122.8 (CTAF)
----------------------------	--	-----------------------	-------------------------------



4 NM Holding Pattern		PELBE	HIBUM	DABLE 2 NM to RW12	RW12	3000 BOPMY
3200 ← 305°		125° →	125°	2600	*1860	*1 NM to RW12
GP 3.00°		TCH 49	6.4 NM	2.3 NM	1 NM	1 NM
CATEGORY	A	B	C	D		
LPV DA	1383-½		200 (200-½)			
LNAV/VNAV DA	1490-½		307 (400-½)			
LNAV MDA	1560-½ 377 (400-½)		1560-⅝ 377 (400-⅝)			
CIRCLING	1640-1 457 (500-1)		1820-1¾ 637 (700-1¾)		1840-2 657 (700-2)	
HIRL Rwy 12-30						
REIL Rws 2 and 20						
MIRL Rwy 2-20						