

WAAS CH 90238 W28A	APP CRS 281°	Rwy Idg TDZE Apt Elev	4103 796 800
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 28


PLYMOUTH MUNI (C65)

RNP APCH - GPS.

Baro-VNAV NA when using South Bend altimeter setting. Rwy 28 helicopter visibility reduction below 1 SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. When local altimeter setting not received, use South Bend altimeter setting and increase LPV DA to 1154 feet and visibility all Cats ¼ SM; LNAV/VNAV DA to 1240 feet and visibility all Cats ¼ SM, increase all MDAs 60 feet and LNAV visibility Cat C ½ SM, and Circling visibility Cat C ¼ SM. Straight-in Rwy 28 NA at night, Circling Rwy 28 NA at night.

MISSED APPROACH: Climb to 3000 direct PHONO and hold.

AWOS-3 133.025	SOUTH BEND APP CON ★ 132.05 257.8	UNICOM 122.975 (CTAF) 0
--------------------------	---	-----------------------------------



3000 PHONO		VGSI and RNAV glidepath not coincident (VGSI Angle 3.30/TCH 28).		4 NM Holding Pattern
↑		TYROS		
SURG		2500		
WEEPS 2.2 NM to RW28		281°		
RW28		1540		
2.2 NM		2.9 NM		
7.1 NM		101°		
6000		281°		
3000		GP 3.05°		
TCH 40				
CATEGORY	A	B	C	D
LPV DA	1103-1	307 (400-1)		NA
LNAV/VNAV DA	1189-1½	393 (400-1½)		NA
LNAV MDA	1260-1	464 (500-1)	1260-1¾ 464 (500-1¾)	NA
CIRCLING	1280-1 480 (500-1)	1360-1 560 (600-1)	1540-2 740 (800-2)	NA