1700

1700

25 DEC

2

SC-1, 27 NOV 2025

TOP ALTITUDE:

ASSIGNED BY ATC

NOTE: DME/DME/IRU or GPS required.

NOTE: RNAV 1.

HOLLE

TAKEOFF MINIMUMS Rwys 3, 18, 21, 36:

Standard with minimum climb of 500' per NM to 1700.

\$\frac{1}{\sqrt{\sq}\}}}\sqrt{\sq}}}}}}}}}}} \end{\sqrt{\sq}}}}}}}}}}}}} \end{\sqrt{\sqrt{\sqrt{\sqrt{\sqrt{\sqrt{\sqrt{\sqrt{\sq}}}}}}}}}}} \end{\sqrt{\sqrt{\sqrt{\sqrt{\sq}}}}}}}}}}} \end{\sq\sintitexent{\sqrt{\sqrt{\sqrt{\sqrt{\sqrt{\sq}}}}}}}}}} \end{\sq

OHYOU *2600 100° (4) *2600 RDHWK *2600 (27)

1700

NOTE: Chart not to scale.

1700

SC-1,

27 NOV 2025 to 25 DEC 2025

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 3: Climb on heading 032° to 1700, then left turn heading 356° or as assigned by ATC, expect RADAR vectors to OHYOU, thence

TAKEOFF RUNWAY 18: Climb on heading 176° to 1700, then heading 176° or as assigned by ATC, expect RADAR vectors to OHYOU, thence

TAKEOFF RUNWAY 21: Climb on heading 212° to 1700, then left turn heading 176° or as assigned by ATC, expect RADAR vectors to OHYOU, thence

TAKEOFF RUNWAY 36: Climb on heading 356° to 1700, then heading 356° or as assigned by ATC, expect RADAR vectors to OHYOU, thence

. . . . on track 100° to RDHWK, then on (transition). Maintain 3000 or as assigned by ATC. Expect filed altitude 10 minutes after departure.

HOLLE TRANSITION (RDHWK3.HOLLE)