

WAAS

CH **66002**

W05A

APP CRS

053°

Rwy Ldg

7001

TDZE

683

Apt Elev

683

RNAV (GPS) RWY 5

CHARLOTTE/MONROE EXEC (EQY)

RNP APCH-GPS.

▼

⚠

Rwy 5 helicopter visibility reduction below $\frac{3}{4}$ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -7°C or above 54°C. Inop table does not apply to LPV all Cats. For inop ALS, increase LNAV/VNAV all Cats visibility to $\frac{1}{2}$ SM and LNAV all Cats visibility to 1 SM.

MALSR

MISSED APPROACH: Climb to 1140 then climbing right turn to 2500 direct MOSEE and hold.

ASOS 135.775	CHARLOTTE APP CON 120.05 307.8	CLNC DEL 132.55	UNICOM 122.7 (CTAF) 0
------------------------	--	---------------------------	---------------------------------

ELEV 683

TDZE 683

HIRL Rwy 5-23 0

REIL Rwy 23 0

	FATED	JAMUN	WUVUL 1.6 NM to RW05	0.9 NM to RW05	RW05
	2500	2500	1220		
	GP 3.00° TCH 46				
	8 NM	4 NM	0.7 NM	0.9 NM	
CATEGORY	A	B	C	D	
LPV DA		933- $\frac{3}{4}$	250 (300- $\frac{3}{4}$)		
LNAV/VNAV DA		1001- $\frac{3}{4}$	318 (400- $\frac{3}{4}$)		
LNAV MDA		1020- $\frac{3}{4}$	337 (400- $\frac{3}{4}$)		
CIRCLING	1220-1	537 (600-1)	1220-1 $\frac{1}{2}$ 537 (600-1 $\frac{1}{2}$)	1480-2 $\frac{1}{2}$ 797 (800-2 $\frac{1}{2}$)	

MONROE, NORTH CAROLINA

Amdt 3A 30NOV23

35°01'N-80°37'W

CHARLOTTE/MONROE EXEC (EQY)

RNAV (GPS) RWY 5