

WAAS CH 99321 W24B	APP CRS 240°	Rwy Idg 5002 TDZE 144 Apt Elev 144
--	------------------------	---

RNAV (GPS) Y RWY 24

CLINTON-SAMPSON COUNTY (CTZ)

RNP APCH-GPS.


▼

⚠

Rwy 24 helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use DPL altimeter setting and increase all MDAs 60 feet and visibility Cats C and D ¼ SM.

MISSED APPROACH: Climb to 2500 direct WEXES and hold.

AWOS-3 119.125	FAYETTEVILLE APP CON 133.0 290.25	UNICOM 122.8 (CTAF) 0
--------------------------	---	---------------------------------



2500

WEXES

VGSI and descent angles not coincident (VGSI Angle 3.00/TCH 40). JASUK

WOGOP 1.8 NM to RW24

EGAPE

4 NM Holding Pattern

3.00° TCH 45

760

1700

2500

1.8

3 NM

5.9 NM

CATEGORY	A	B	C	D
LP MDA	560-1	416 (500-1)	560-1½	416 (500-1½)
LNAV MDA	640-1	496 (500-1)	640-1¾	496 (500-1¾)
CIRCLING	680-1 536 (600-1)	780-1 636 (700-1)	840-2 696 (700-2)	840-2¼ 696 (700-2¼)

