

WAAS CH 42615 W15A	APP CRS 146°	Rwy Idg TDZE Apt Elev	4000 1025 1025
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 15


PLATTEVILLE MUNI (PVB)

RNP APCH - GPS.

▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C (2°F) or above 54°C (130°F).
▲ When local altimeter setting not received, use DBQ altimeter setting and increase LPV DA to 1331 feet; increase LNAV/VNAV DA to 1394 feet; increase all MDA's 60 feet and LNAV visibility Cat C ¼ SM, and Circling visibility Cat C ¼ SM. Baro-VNAV and VD NA when using Dubuque altimeter setting. Circling Rwy 7, 25 NA at night.

MISSED APPROACH:
Climb to 3000 direct
ZAWDI and hold.

AWOS-3 120.575	CHICAGO CENTER 133.95 281.4	UNICOM 122.7 (CTAF) 0
--------------------------	---------------------------------------	---------------------------------



4 NM Holding Pattern

3000 ← 326°
146° →

GP 3.00°
TCH 40

CEWUF

TANCI

3000

1.6 NM to RW15

RW15

CATEGORY	A	B	C	D
LPV DA	1275-1	250 (300-1)		NA
LNAV/VNAV DA	1338-1	313 (400-1)		NA
LNAV MDA	1560-1	535 (600-1)	1560-1½ 535 (600-1½)	NA
CIRCLING	1560-1 535 (600-1)	1600-1 575 (600-1)	1600-1½ 575 (600-1½)	NA

