

<div>MIAMI DEP CON 126.05 251.1 ATIS 120.55 GND CON 121.9 POMPANO BEACH TOWER ★ 125.4 (CTAF)</div>	<div>TOP ALTITUDE: ASSIGNED BY ATC</div>	<div>RNAV 1 - DME/DME/IRU or GPS. RADAR required.</div>
--	--	---

ONEWY

MATLK

FUNNR

BENNS

DORRL

BOGY

LIFRR 4000

FL180
3000
(16)

FL180
1500
(15)

FL1200
1500
(26)

FL1000
1600
(34)

005°
(11)

002°
(9)

MSA PMP 25 NM
2600

330°

060°

285°

105°

240°

150°

NOTE: For turbo-props/props filed at or above 13000.

TAKEOFF MINIMUMS

Rwys 6, 10, 15, 24, 28, 33: Standard with minimum climb of 500'/NM to 520.

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 6: Climb on heading 060° or as assigned by ATC for RADAR vectors to cross LIFRR at or above 4000, thence. . .

TAKEOFF RUNWAY 10: Climb on heading 105° or as assigned by ATC for RADAR vectors to cross LIFRR at or above 4000, thence. . .

TAKEOFF RUNWAY 15: Climb on heading 150° or as assigned by ATC for RADAR vectors to cross LIFRR at or above 4000, thence. . .

TAKEOFF RUNWAY 24: Climb on heading 240° or as assigned by ATC for RADAR vectors to cross LIFRR at or above 4000, thence. . .

TAKEOFF RUNWAY 28: Climb on heading 285° or as assigned by ATC for RADAR vectors to cross LIFRR at or above 4000, thence. . .

TAKEOFF RUNWAY 33: Climb on heading 330° or as assigned by ATC for RADAR vectors to cross LIFRR at or above 4000, thence. . .

. . . on track 002° to BOGY, then on track 005° to DORRL then on (transition), maintain altitude as assigned by ATC, expect filed altitude 10 minutes after departure.

MATLK TRANSITION (DORRL2.MATLK)

ONEWY TRANSITION (DORRL2.ONEWY)

NOTE: Chart not to scale.

DORRL TWO DEPARTURE (RNAV)
(DORRL2.DORRL) 21MAR24

POMPANO BEACH, FLORIDA
POMPANO BEACH AIRPARK (PMP)

SE-3, 27 NOV 2025 to 25 DEC 2025

SE-3, 27 NOV 2025 to 25 DEC 2025