

WAAS CH 82208 W09A	APP CRS 092°	Rwy Idg TDZE Apt Elev	4201 912 913
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 9

DE KALB TAYLOR MUNI (DKB)


▼

⚠

When local altimeter setting not received, use Aurora altimeter setting and increase all DA 61 feet and all MDA 80 feet; increase all LPV and LNAV/VNAV visibilities, LNAV Cats C/D visibility, and Circling Cats C/D visibility ¼ mile. Baro-VNAV NA when using Aurora altimeter setting. VDP NA when using Aurora altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 47°C (116° F). DME/DME RNP-0.3 NA. Visibility reduction by helicopters NA.

MISSED APPROACH: Climb to 3000 direct OPIKE and hold.

AWOS-3 119.075	CHICAGO APP CON 133.5 349.0	UNICOM 122.7 (CTAF) 0
--------------------------	---------------------------------------	---------------------------------



Procedure Turn NA	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 30).				3000 ↑	OPIKE 
CASHO	KRONE				*LNAV only.	
2500	2500					
GP 3.00° TCH 45	*1.6 NM to RW09					
6.1 NM		3.2 NM		1.6		
CATEGORY	A	B	C	D		
LPV DA	1186-1 274 (300-1)					
LNAV/ VNAV DA	1543-2¼ 631 (700-2¼)					
LNAV MDA	1460-1 548 (600-1)		1460-1½ 548 (600-1½)		1460-1¾ 548 (600-1¾)	
CIRCLING	1460-1 547 (600-1)	1500-1 587 (600-1)	1600-2 687 (700-2)		1740-2¾ 827 (900-2¾)	

ELEV 913	TDZE 912
REIL Rwy 9, 20 and 27 0	
MIRL Rwy 2-20	
MIRL Rwy 9-27 0	