

RNAV (GPS) RWY 29

KANSAS CITY/LEE'S SUMMIT RGNL (LXT)

⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. VDP and Baro-VNAV NA when using Kansas City Downtown/Wheeler Fld altimeter setting. When local altimeter setting not received, use Kansas City Downtown/Wheeler Fld altimeter setting: increase LPV DA to 1322 feet; increase LNAV/VNAV DA to 1359 feet; increase all MDA 80 feet and visibility Cats C and D ¼ SM.

MISSED APPROACH: Climb to 1500 then climbing right turn to 3000 direct LYMES and hold.

Diagram illustrating a flight path or mission profile, showing various waypoints, altitudes, and distances.

Waypoints and Altitudes:

- 2049 (multiple instances)
- 2044
- 2038
- 1477
- 1051±
- 1125
- RW29
- ZEVED (1.7 NM to RW29)
- 291°
- (FAF) PUKAS
- 2600
- 292° (7)
- (IF/IAF) ZONKI
- 112°

Distances and Angles:

- 30 NM to ZONKI
- 30 NM to ZONKI (NoPT)
- 022°
- 202°
- 4 NM

Legend:

- MISSED APCH FIX (Triangle symbol)
- LYMES (Circle symbol)
- 269°
- 089°
- 4 NM

Table:

ELEV 1004	TDZE 1004
-----------	-----------

CATEGORY	A	B	C	D
LPV DA	1254-1	250 (300-1)		
LNAP/ VNAP DA	1291-1	287 (300-1)		
LNAP MDA	1360-1	356 (400-1)		
CIRCLING	1440-1 436 (500-1)	1540-1 536 (600-1)	1780-2¼ 776 (800-2¼)	1780-2½ 776 (800-2½)

KANSAS CITY/LEE'S SUMMIT RGNL (LXT)
RNAV (GPS) RWY 29