

Baro-VNAV NA. Circling Rwy 13, 31 NA at night. DME/DME RNP-0.3 NA. Use Lubbock altimeter setting. When not received, use Seminole altimeter setting and increase LPV DA to 3600; increase LNAV/VNAV DA to 3600; and increase all MDA 20 feet.

MISSED APPROACH: Climb to 5200 direct LEBDE and hold.

LBB ASOS 125.3 270.275	LUBBOCK APP CON 119.2 351.8	UNICOM 122.8 (CTAF) 0
---------------------------	--------------------------------	--------------------------

MISSED APCH FIX
5 NM
LEBDE

30 NM to WOGFE
15 NM to WOGFE
5300
5000
WOGFE
107°
287°
30 NM to WOGFE
15 NM to WOGFE
5000
5300
WOGFE (NoPT)
107°
287°

3739
3533
3840
3301±
RW02
SLOBS 2.4 NM to RW02
(FAF) FATYO
4900
017°
(6)
(IF/IAF) WOGFE
017°
197°
5 NM

5 NM Holding Pattern
WOGFE
5000
197°
017°
017°
4900
FATYO
SLOBS 2.4 NM TO RW02
RW02
5200 LEBDE
*LNAV only.
GP 3.00°
TCH 43
6 NM
2.6 NM
2.4 NM
*4060

ELEV 3265
TDZE 3256

20
15
10
5
2
017°
27.65 X 7.5
5218 X 7.5
0.4% UP
MIRL Rwy 2-20

CATEGORY	A	B	C	D
LPV DA		3589-1	333 (400-1)	
LNAV/VNAV DA		3589-1	333 (400-1)	
LNAV MDA	3640-1	384 (400-1)	3640-1½	384 (400-1½)
CIRCLING	3760-1 495 (500-1)	3920-1 655 (700-1)	3980-2 715 (800-2)	4100-2¾ 835 (900-2¾)

BROWNFIELD, TEXAS

33°10'N-102°12'W

TERRY COUNTY (BFE)

Amtd 1 29MAR18

RNAV (GPS) RWY 2