


WAAS CH 70523 W28A	APP CRS 277°	Rwy Idg 3013 TDZE 237 Apt Elev 237
--	------------------------	---

RNAV (GPS) RWY 28

OAKDALE (O27)

RNP APCH-GPS.	MISSED APPROACH: Climb to 7000 direct ZOSON and on track 328° to LIN VOR/DME and hold, continue climb-in-hold to 7000.
▼ NA Rwy 28 helicopter visibility reduction below ¼ SM NA. Baro-VNAV NA. Use Modesto altimeter setting; when not received, use Stockton altimeter setting: increase LPV DA to 581 feet and all visibilities ⅛ SM; increase LNAV/VNAV DA to 728 feet; increase all MDAs 40 feet.	

MOD ASOS 127.7	NORCAL APP CON 125.1 363.2	UNICOM 122.8 (CTAF) 0
--------------------------	--------------------------------------	---------------------------------



ELEV 237	TDZE 237
----------	----------

REIL Rwy 10 and 28 MIRL Rwy 10-28 0	7000	ZOSON	tr 328°	LIN	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 25).				4 NM Holding Pattern
					NOMAE	WUMTA			
					1800	288°	108°	6000	2000
					RW28	277°	288°	1800	
					4.7 NM	3 NM			GP 3.00° TCH 53
CATEGORY		A	B	C	D				
LPV DA		547-7⅞		310 (400-7⅞)		NA			
LNAV/VNAV DA		694-1⅓		457 (500-1⅓)		NA			
LNAV MDA		820-1	583 (600-1)		820-1⅓	583 (600-1⅓)		NA	
CIRCLING		820-1	583 (600-1)		920-2	683 (700-2)		NA	