

WAAS CH 82404 W28A	APP CRS 281°	Rwy Idg TDZE Apt Elev	4001 928 928
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 28

MIDDLETON MUNI/MOREY FLD (C29)

RNP APCH - GPS.


▼

▲


Baro-VNAV NA. Helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Dane County Rgnl/Truax Fld altimeter setting. VDP NA when using Dane County Rgnl/Truax Fld altimeter setting. Circling NA to Rwy's 1 and 19.

MISSED APPROACH:
Climb to 4000 direct JALOX and hold.

AWOS-3 118.675	MADISON APP CON ★ 135.45 343.7	UNICOM 123.0 (CTAF) 0
--------------------------	--	---------------------------------



ELEV 928	TDZE 928
----------	----------



4000	JALOX	VGSI and RNAV glidepath not coincident (VGSI Angle 4.00/TCH 36).				EXIDE	4 NM	Holding Pattern
				CAVEX	GUZBY	EXIDE	101°	4000
		1.2 NM to RW28		2600	3500		281°	
		1.2 NM	3.9 NM	3 NM	3 NM			GP 3.00° TCH 40
CATEGORY	A	B	C	D				
LPV DA	1326-1½		398 (400-1½)		NA			
LNAV/VNAV DA	1442-1¾		514 (600-1¾)		NA			
LNAV MDA	1480-1		552 (600-1)		1480-1½		552 (600-1½)	
CIRCLING	1560-1		1640-1		1660-2		NA	
	632 (700-1)		712 (800-1)		732 (800-2)			