

WAAS
CH **70614**
W17A

APP CRS
172°

Rwy Idg
TDZE **2176**
Apt Elev **2189**

RNAV (GPS) RWY 17
WEST WOODWARD (WWR)

RNP APCH

Baro-VNAV and VDP NA when using Gage altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C or above 54°C. When local altimeter setting not received, use Gage altimeter setting and increase all DA/MDA 40 feet. Inop table does not apply. Circling Rwy 5, 23 NA at night.

ODALS

MISSED APPROACH:
Climb to 4500 direct
TISSY and hold.

AWOS-3 118.425	KANSAS CITY CENTER 126.95 379.2	UNICOM 122.8 (CTAF) 0
--------------------------	---	---------------------------------

ELEV 2189

TDZE 2176

172°

2500 X 60

5502 X 100

2230

35

4500

TISSY

△

*LNAV only.

*1.6 NM to RWY 17

RUNSY

OHFEB

3800

4000

GP 3.00°

TCH 39

CATEGORY	A	B	C	D
LPV DA	2426-1	250 (300-1)		
LNAV/VNAV DA	2572-1½	396 (400-1½)		
LNAV MDA	2700-1 524 (600-1)	2700-1½ 524 (600-1½)	2700-1¾ 524 (600-1¾)	2700-2 524 (600-2)
CIRCLING	2700-1 511 (600-1)	2860-1 671 (700-1)	2940-2¼ 751 (800-2¼)	2960-2½ 771 (800-2½)

WOODWARD, OKLAHOMA

Orig-B 07OCT21

36°26'N-99°31'W

WEST WOODWARD (WWR)

RNAV (GPS) RWY 17