

WAAS

CH **62812**

W17A

APP CRS

170°

Rwy Idg

4400

TDZE

769

Apt Elev

769

RNAV (GPS) RWY 17

HANNIBAL RGNL (HAE)

▼

▲ NA

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Visibility reduction by helicopters NA. When local altimeter setting not received, use Quincy altimeter setting; increase all DA 41 feet, all MDA 60 feet, increase LNAV Cat C visibility ¼ SM and Circling Cat C visibility ¼ SM. Baro-VNAV and VDP NA when using Quincy altimeter setting.

MISSED APPROACH: Climb to 3000 direct PARCK and hold.

AWOS-3PT 120.775	KANSAS CITY CENTER 126.225 317.775	UNICOM 122.8(CTAF) 0
----------------------------	--	--------------------------------

4 NM Holding Pattern		DORUW		LAMOO		OBEDE 2.5 NM to RW17		PARCK	
3000		← 350°		→ 170°		170°		*INAV only	
GP 3.00°		TCH 40		2400		*1600		*1 NM to RW17	
		6.1 NM		2.5 NM		1.5 NM		1 NM	
CATEGORY		A		B		C		D	
LPV DA		1019-1 250 (300-1)				NA			
LNAV/VNAV DA		1079-1¼ 310 (400-1¼)				NA			
LNAV MDA		1120-1 351 (400-1)				NA			
CIRCLING		1260-1 491 (500-1)		1640-2½ 871 (900-2½)		NA			

ELEV 769

TDZE 769

170°

400 x 100

35

MIRL Rwy 17-35 0

REIL Rwy 17 and 35 0

HANNIBAL, MISSOURI

Orig-A 25MAR21

39°44'N-91°27' W

HANNIBAL RGNL (HAE)

RNAV (GPS) RWY 17