

WAAS CH 57912 W35A	APP CRS 353°	Rwy Idg TDZE 892 Apt Elev 892	5799
--	------------------------	---	-------------

RNAV (GPS) RWY 35

WILLIAM R POGUE MUNI (OWP)

RNP APCH - GPS.

▼

Rwy 35 helicopter visibility reduction below ¾ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. Circling NA for Cat C east of Rwy 17-35.

⚠



Inop table does not apply to LPV all Cats. When local altimeter setting not received, use TUL altimeter setting and increase LPV DA to 1209 feet, increase LNAV/VNAV DA to 1244 feet and all visibilities ½ SM. Increase all MDAs 80 feet and LNAV visibility Cat C ¼ SM. Baro-VNAV and VDP NA when using TUL altimeter setting.

ODALS

⬢

MISSED APPROACH: Climb to 2800 direct WEDAX and hold.

AWOS-3T 118.325	TULSA APP CON 124.0 338.3	UNICOM 122.7 (CTAF) 0
---------------------------	-------------------------------------	--



2800	WEDAX	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 33).		4 NM
		PENNN 2.7 NM to RW35	FANCY 2400	ACERT Holding Pattern
		1.1 NM to RW35		173° → 6000
				← 353° 2800
				GP 3.00° TCH 45
		1.1 NM	1.6 NM	1.9 NM
				6.4 NM
CATEGORY	A	B	C	D
LPV DA	1142-¾	250 (300-¾)		NA
LNAV/VNAV DA	1177-¾	285 (300-¾)		NA
LNAV MDA	1280-¾	388 (400-¾)	1280-1 388 (400-1)	NA
CIRCLING	1380-1	488 (500-1)	1400-1½ 508 (600-1½)	NA

SC-1, 27 NOV 2025 to 25 DEC 2025

SC-1, 27 NOV 2025 to 25 DEC 2025