

LOC/DME	I-EYK	APP CRS	Rwy Ldg
111.7		048°	5500
Chan 54			TDZE 18
			Apt Elev 19

ILS or LOC RWY 5

CHESAPEAKE RGNL (CPK)

⚠

When local altimeter setting not received, use ORF altimeter setting and increase DA to 256 feet; increase all MDAs 40 feet and CEKAD fix minimums S-LOC 5 visibility Cats C and D 1½ SM. For inop ALS, increase S-LOC 5 Cats C and D visibility to 1¾ SM.

MALSR

MISSED APPROACH: Climb to 500 then climbing left turn to 2000 on heading 190° and ORF VORTAC R-216 to NALDE INT/I-EYK 12.3 DME and hold.

AWOS-3 123.675	NORFOLK APP CON 118.9 353.7	GCO 135.075	UNICOM 123.075 (CTAF) 0
-------------------	--------------------------------	----------------	----------------------------

ELEV 19	TDZE 18
---------	---------

One Minute Holding Pattern

NALDE INT
I-EYK 12.3

TAVAE INT
I-EYK 6.2

CEKAD
I-EYK 2.6

I-EYK 1.1

4000

2000

GS 3.00°
TCH 43

228°

048°

048°

1700

1700

6.1 NM

3.7 NM

1.5 NM

500

2000

hdg 190°

ORF R-216

NALDE INT

*520 when using ORF altimeter setting.

CATEGORY	A	B	C	D
S-ILS 5		218-½	200 (200-½)	
S-LOC 5	480-½	462 (500-½)	480-1	462 (500-1)
CIRCLING	480-1	461 (500-1)	520-1½ 501 (600-1½)	580-2 561 (600-2)
CEKAD FIX MINIMUMS				
S-LOC 5	400-½	382 (400-½)	400-5⁄8	382 (400-5⁄8)
CIRCLING	460-1 441 (500-1)	480-1 461 (500-1)	520-1½ 501 (600-1½)	580-2 561 (600-2)

NORFOLK, VIRGINIA

Amtd 2 27NOV25

36°40'N-76°19'W

CHESAPEAKE RGNL (CPK)

ILS or LOC RWY 5