

WAAS CH 82600 W11A	APP CRS 109°	Rwy Ldg TDZE 310 Apt Elev 310
--	------------------------	---


RNAV (GPS) RWY 11

SOUTH ALABAMA RGNL AT BILL BENTON FLD (79J)


⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Cairns AAF (Fort Rucker) altimeter setting and increase all DA 82 feet, all MDA 100 feet. Increase all LPV and LNAV/VNAV visibilities ¾ mile all Cats, LNAV and Circling Cats C and D ½ mile. Baro-VNAV and VDP NA when using Cairns AAF (Fort Rucker) altimeter setting.

MISSED APPROACH: Climb to 2000 direct ALANE and hold.

ASOS 134.875	CAIRNS APP CON ★ 133.45 239.275	UNICOM 122.8 (CTAF) 0
------------------------	---	--



4 NM Holding Pattern		VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 33).		2000 ALANE	
2500		HIDAR		*1300	
GP 3.00° TCH 40		YERUS 3 NM to RW11		*1.3 NM to RW11	
289°		2000		RW11	
109°		6 NM		2.2 NM	
109°		1.7 NM		1.3 NM	
CATEGORY		A	B	C	D
LPV DA		615-1		305 (400-1)	
LNAV/VNAV DA		655-1½		345 (400-1½)	
LNAV MDA		760-1	450 (500-1)	760-1¾	450 (500-1¾)
CIRCLING		820-1	510 (600-1)	860-1½	940-2
				550 (600-1½)	630 (700-2)



SE-4, 27 NOV 2025 to 25 DEC 2025

SE-4, 27 NOV 2025 to 25 DEC 2025