

(DAWNN1.DAWNN) 23334
DAWNN ONE DEPARTURE

AL-6614 (FAA)

INDY SOUTH GREENWOOD (HFY)
INDIANAPOLIS, INDIANA

AWOS-3P
118.525
INDIANAPOLIS DEP CON
124.95 317.8

BRICKYARD
116.3 VHP
Chan 110

TOP ALTITUDE:
ASSIGNED BY ATC

TERRE HAUTE
115.3 TTH
Chan 100


HOOSIER
110.2 OOM
Chan 39

SNEVA
RADAR

FOYTT
RADAR

DAWNN
10000
(For LOUISVILLE Transition)

TAKEOFF MINIMUMS:
Rwy 1: Standard.
Rwy 19: 300-1 or standard with minimum
climb of 484' per NM to 1200.



LOUISVILLE
114.8 IU
Chan 95

MYSTIC
108.2 MYS

- NOTE: RADAR required.
NOTE: Select appropriate localizer/DME frequency/channel prior to departure.
NOTE: Turbojets accelerate to 250K until reaching 10000, if unable advise ATC.
NOTE: Assigned to aircraft with a requested altitude of 11000 or above.

(NARRATIVE ON FOLLOWING PAGE)

NOTE: Chart not to scale.



DEPARTURE ROUTE DESCRIPTION

TAKEOFF RWY 1: Climb heading 010° to 1500 before turning right. Then on assigned heading to assigned altitude. Thence....

DEPARTING ALL OTHER AUTHORIZED RUNWAYS/AIRPORTS: Climb on assigned heading to assigned altitude. Thence....

....on RADAR vectors to join VHP R-174 to DAWNN INT then on transition or assigned route. Expect clearance to requested altitude ten minutes after departure.

LOUISVILLE TRANSITION (DAWNN1.IIU): From over DAWNN INT on IIU R-311 to IIU VORTAC.

MYSTIC TRANSITION (DAWNN1.MYS): From over DAWNN INT on MYS R-002 to MYS VOR.

EC-2, 27 NOV 2025 to 25 DEC 2025

EC-2, 27 NOV 2025 to 25 DEC 2025